

Guard





















Guard

Guard is a nice and luxurious high-quality fabric, woven on a dobby loom and part of the Textaafoam Performance Collection.

This collection only consists of fabrics that meet the highest standards in durability and maintenance, making them long lasting, easy to clean and suitable for almost every type of upholstery.

Stains can easily be taken away with nothing more than a damp cloth. No wonder this article meets all requirements of our specialty Easy Clean Collection; www.picobello-fabrics.com.

This luxurious fine woven textile meets every style and is suitable for fitted and loose fitting upholstery. The chenille provides an extra soft handfeel and it has a full and rich appearance.

Please kindly note that due to these chenille yarns, shading and sitting mirror (seat depression) will appear, this can be minimized by brushing the fabric regularly or vacuum clean (low power) with an upholstery nozzle with and against the pile.

Full rolls are delivered in a suspended box and cutlengths are wrapped in bubblewrap to minimize the pressure, when a pressure mark is noticed, due to transport, handling or storage. Kindly brush several times against the pile, tension may be used. Please also give it some time so the pile can go back to its original position.

Sitting mirror is a property of these kind of qualities and has no influence on the durability of this fabric.

Guard is also machine-washable at 30 degrees Celsius.

- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.

Textaafoam originals Established in 1970, this Dutch family business brings together craftsmen in textiles and furniture design to build an unrivalled portfolio in upholstery fabrics that meets buyer's needs every time. Featuring a wide colour range, ultimate value for money and excellent reliability in the supply chain.

Composition

/ faceside 100%PES / backside n/a / chenille flatweave





Please note: colours may vary according to your screen settings.





taupe 12

Guard - Article passport

Packaging

A nice luxurious high-quality article that meets every style.

Available from stock in a wide range of contemporary and commercial colours.

| Product characteristics | | |
|-------------------------|---|--|
| Productgroup | chenille flatweave | |
| Applications | sofa's, beds, chairs with fitted and loose fitting upholstery | |
| Composition faceside | 100%PES | |
| Composition backside | n/a | |
| Coating | needle punch | |
| Statistic code | 58013300 | |
| Dyeing method | yarn dyed | |
| Available colours | 19 | |

| Test | Test specification | Executed by laboratory: | Unit | Testresult | | Norm RAL GZ 430/4:2019-01 | | Norm DIN EN 14 465:2006-09 | |
|-------------------------------------|--|-------------------------|--------|------------|--------|---------------------------|-----------------------|-------------------------------|--|
| | | | | Dry | Wet | DGM | DGM+ | 100.200 | |
| Abrasion resistance - yarn breakage | DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03 | CTL | cycles | >100.000 | | min. 8.000 | min. 16.000 | С | |
| Pilling | DIN EN ISO 12945-2:2000-11. 2000 cycles | CTL | grade | 4 | | min. 3-4 | min. 4 | В | |
| Colour fastness to light | DIN EN ISO 105-B02:2014-11. Process 3, exposure level 5 | | | | | | | | |
| | light colours | CTL | grade | 4 | | min. 4 | min.5 | С | |
| | middle colours | CTL | grade | 4 | | min. 4 | min.5 | С | |
| | dark colours CTL grade | | 4-5 | | min. 4 | min.5 | B-C | | |
| Colour fastness to rubbing | DIN EN ISO 105-X12:2016-11 | | | | | | | | |
| | light colours | CTL | grade | 4-5 | 4-5 | dry: 4, wet: 3 | dry: > 4, wet: 3-4 | A/A | |
| | middle colours | CTL | grade | 4-5 | 5 | dry: 4, wet: 3 | dry: > 4, wet: 3-4 | A/A | |
| | dark colours | CTL | grade | 4-5 | 4-5 | dry: 4, wet: 3 | dry: > 4, wet: 3-4 | A/A | |
| gnitability (cigarette test) | BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 4 part 1 Ignition source 0: cigarette | СТL | | pa | ssed | | | | |

| Processing specifications | | | | | | | | |
|---|---|-------------------------|--------|------------|------|---------------------------|----------|-------------------------------|
| Minimum workable width in centimeters | ± 138 | | | | | | | |
| Roll length in meters | ± 40 | | | | | | | |
| Material weight in grams per linear meter | ± 580 | | | | | | | |
| Test | Test specification | Executed by laboratory: | Unit | Testresult | | Norm RAL GZ 430/4:2019-01 | | Norm DIN EN 14 465:2006-09 |
| | | | | Warp | Weft | DGM | DGM+ | |
| Tensile strength | DIN EN ISO 13934-1:2013-08 | CTL | Newton | 1.629 | 419 | min. 350 | min. 400 | A/B |
| Tear growth resistance | DIN EN ISO 13937-3:2000-06 | CTL | Newton | 128,9 | 35,2 | min. 25 | min. 30 | A/B |
| Resistance to seam slippage | DIN EN ISO 13936-2:2004-07. Load 180 N | CTL | mm | 2,5 | 2,8 | max. 5 | max. 4 | A/A |
| Delamination | DIN 53530:1981-02 | CTL | Newton | n/a | n/a | n/a | n/a | n/a |
| Chemical substances | REACH | Centexbel | | passed | | | • | |

Centexbel

Cleaning specifications

| Test | Test specification | Executed by laboratory: | Unit | Testresult | | Norm RAL GZ 430/4:2019-01 | | Norm DIN EN 14 465:2006-09 |
|--|---|-------------------------|------|------------|------|---------------------------|------|-------------------------------|
| | | | | Warp | Weft | DGM | DGM+ | |
| Dimensional change for washing 30 degrees celcius / air drying | DIN EN ISO 5077:2008-04, DIN EN ISO 6330:2013-02, DIN EN ISO 3759:2011-08 | CTL | % | -0,7 | -0,6 | n/a | n/a | A/A |


















certified













Oeko-Tex, product class II