



Pebble





Pebble

This soft quality is a proud member of our Comfort Collection. A collection that consists only of soft, voluminous, and elegant upholstery fabrics.

Pebble is 100% softness made of virgin polyester and this voluminous textile will fulfill your wishes for comfort and coziness. The subtle high-low structure gives an amazing appearance to the sofa, chair, and bed.

Easy to upholster and no need to worry about loops, this flatwoven chunky fabric is made of twisted chenille yarns. Due to these yarns, sitting mirror and shading will appear during usage, this can be minimized by brushing the fabric on a regular base (mainly) against the pile. These properties belong to pile fabrics such as Pebble.

Pebble has a distinct nap/ pile direction, which is inherently influenced by the loom and the type of yarns (twisted chenille/ pile). It is rather challenging to avoid/ control this entirely, due to the fact it's woven in a certain V-direction, which means that side-center-side colour deviations are unavoidable. To minimize this, we recommend to maintain a consistent nap/ pile direction during cutting and try to avoid placing opposing nap/ pile directions together in the same upholstered furniture.

The complete colour range has been developed by looking at the latest trend. Even in light colours it is easy to clean and maintain, laminated with a bonding for extra body and easy to upholster.

Pebble is also machine-washable at 30 degrees Celsius*.

Try Pebble and you will be impressed by the look, incredible touch, and elegance.

- Always be careful with sharp or rough objects such as watches, buckles, or Velcro, as they may damage the fabric.

- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.

***Textrafoam originals** Established in 1970, this Dutch family business brings together craftsmen in textiles and furniture design to build an unrivalled portfolio in upholstery fabrics that meets buyer's needs every time. Featuring a wide colour range, ultimate value for money and excellent reliability in the supply chain.*

Composition

/ faceside 100%PES
/ backside 100%PES
/ flatweave

Suitable for

sofa's, beds, chairs with fitted and loose fitting upholstery



beige 05



brass 170



brown 15



burgundy 34



butter 222



ecru 102



herb 214



lightgrey 60



natural 01



olive 53



plumb 168



sage 203

Please note: colours may vary according to your screen settings.



shell 196



shitake 124



stone 181



taupe 12



teal 198

Please note: colours may vary according to your screen settings.

Pebble - Article passport

Pebble is a voluminous textile with a subtle high-low structure.

Available from stock in a wide range of contemporary and commercial colours.

Product characteristics

Productgroup	flatweave	
Applications	sofa's, beds, chairs with fitted and loose fitting upholstery	
Composition faceside	100%PES	
Composition backside	100%PES	
Bonding	pongee backing	
Statistic code	54075200	
Dyeing method	piece dyed	
Available colours	17	
Packaging	bubble wrap	

Durability specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Dry	Wet	DGM	DGM+	
Abrasion resistance - yarn breakage	DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	CTL	cycles	>100.000		min. 16.000	min. 25.000	A
Pilling	DIN EN ISO 12945-2:2000-11. 2000 cycles	CTL	grade	4-5		min. 3-4	min. 4	A
Colour fastness to light	DIN EN ISO 105-BO2:2014-11. Process 3, exposure level 5							
	light colours	CTL	grade	5		min. 4	min.5	B
	middle colours	CTL	grade	5		min. 4	min.5	B
	dark colours	CTL	grade	5		min. 4	min.5	B
Colour fastness to rubbing	DIN EN ISO 105-X12:2016-11							
	light colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
	middle colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
	dark colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
Ignitability (cigarette test)	 BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 4 part 1 Ignition source 0: cigarette	CTL		passed				

Processing specifications

Minimum workable width in centimeters	± 138							
Roll length in meters	± 40							
Material weight in grams per linear meter	± 539							
Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Tensile strength	DIN EN ISO 13934-1:2013-08	CTL	Newton	1.016	659	min. 350	min. 400	A/A
Tear growth resistance	DIN EN ISO 13937-3:2000-06	CTL	Newton	79,9	84,2	min. 25	min. 30	A/A
Resistance to seam slippage	DIN EN ISO 13936-2:2004-07. Load 180 N	CTL	mm	2,3	1,3	max. 5	max. 4	A/A
Delamination	DIN 53530:1981-02	CTL	Newton	13,5	21,7	n/a	n/a	n/a
Chemical substances	REACH	Centexbel		passed				
	Oeko-Tex, product class II	Centexbel		certified				

Cleaning specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Dimensional change for washing 30 degrees celcius / air drying	DIN EN ISO 5077:2008-04, DIN EN ISO 6330:2013-02, DIN EN ISO 3759:2011-08	CTL	%	-1,2	-1,0	n/a	n/a	A/A
 - We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.								



Textaafoam b.v.
La Défense 11 | 5026 SC Tilburg
P.O. Box 12 | 5050 AA Goirle
The Netherlands

T +31(0)13 534 5934
F +31(0)13 534 7586
E info@textaafoam.nl
www.textaafoam.nl