



Crisp





Crisp

Crisp is a genuine style icon in our comfort collection. Softness, volume, and elegance are just some of the characteristics for this type of qualities.

We have succeeded to create a fabric with the atmosphere of carefree maintenance, to enjoy your furniture to the fullest. This slightly shiny soft chenille textile has a subtle and elegant look and is a true treat to the touch. An elegant pattern/ slub texture is visible in this piece dyed textile and it creates a very natural appearance on each type of model.

Due to the chenille yarns, sitting mirror and shading will appear during usage, this can be minimized by brushing the fabric on a regular base (mainly) against the pile.

The fabric is a flat-woven quality of 100% polyester with a light back coating and C0 easyclean finish. The piece dyed colour range is developed in a full range of natural tones and warm deep colourshades that represent the latest interior fashion trends.

Thanks to the combination of the yarns and finish (PFAS free), it is also in the www.picobello-fabrics.com collection. Easy to clean, easy to maintain and even machine-washable at 30 degrees Celsius*.

Due to the more rough construction of Crisp, we recommend a minimum seam allowance of minimum 1 cm. Another kind advice is to overlock all seams for more stability, especially with tight upholstered furniture.

Each type of furniture will look and stay fabulous in any Crisp colour.

- Please note that due to chenille yarns, shading and seat depression are possible.

- Dirt and damp prevention treatment applied.

- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.

- Please note that during washing the damp- and dirt prevented treatment will disappear faster.

Textafoam originals Established in 1970, this Dutch family business brings together craftsmen in textiles and furniture design to build an unrivalled portfolio in upholstery fabrics that meets buyer's needs every time. Featuring a wide colour range, ultimate value for money and excellent reliability in the supply chain.

Composition

/ faceside 100%PES
/ backside n/a
/ chenille flatweave

Suitable for

sofa's, beds, chairs with fitted and loose fitting upholstery



brandy 127



burgundy 034



butter 222



caramel 016



chocolate 017



clay 084



curry 216



ecru 102



hazel 096



linen 110



liver 010



natural 001

Please note: colours may vary according to your screen settings.




olive 053



sage 203



shell 196



slate 087



teal 198

Please note: colours may vary according to your screen settings.

Crisp - Article passport

A slightly shiny soft chenille textile with a subtle and elegant look.

Available from stock in a wide range of contemporary and commercial colours.

Product characteristics

Productgroup	chenille flatweave	
Applications	sofa's, beds, chairs with fitted and loose fitting upholstery	
Composition faceside	100%PES	
Composition backside	n/a	
Coating	transparent	
Statistic code	58013600	
Dyeing method	piece dyed	
Available colours	17	
Packaging	boxes	

Durability specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Dry	Wet	DGM	DGM+	
Abrasion resistance - yarn breakage	DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	CTL	cycles	50.000		min. 12.000	min. 16.000	B
Pilling	DIN EN ISO 12945-2:2000-11. 2000 cycles	CTL	grade	4-5		min. 3-4	min. 4	A
Colour fastness to light	DIN EN ISO 105-BO2:2014-11. Process 3, exposure level 5							
	light colours	CTL	grade	4-5		min. 4	min.5	B-C
	middle colours	CTL	grade	4-5		min. 4	min.5	B-C
	dark colours	CTL	grade	4-5		min. 4	min.5	B-C
Colour fastness to rubbing	DIN EN ISO 105-X12:2016-11							
	light colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
	middle colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
	dark colours	CTL	grade	4-5	4-5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
Ignitability (cigarette test)	 BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 4 part 1 Ignition source 0: cigarette	CTL		passed				

Processing specifications

Minimum workable width in centimeters	± 142							
Roll length in meters	± 35							
Material weight in grams per linear meter	± 600							
Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Tensile strength	DIN EN ISO 13934-1:2013-08	CTL	Newton	2.043	1.091	min. 350	min. 400	A/A
Tear growth resistance	DIN EN ISO 13937-3:2000-06	CTL	Newton	119,8	64,1	min. 25	min. 30	A/A
Resistance to seam slippage	DIN EN ISO 13936-2:2004-07. Load 180 N	CTL	mm	2,2	2,8	max. 5	max. 4	A/A
Delamination	DIN 53530:1981-02	CTL	Newton	n/a	n/a	n/a	n/a	n/a
Chemical substances	REACH	Centexbel		passed				
	Oeko-Tex, product class II	Centexbel		certified				

Cleaning specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Dimensional change for washing 30 degrees celcius / air drying	DIN EN ISO 5077:2008-04, DIN EN ISO 6330:2013-02, DIN EN ISO 3759:2011-08	CTL	%	-0,4	-0,4	n/a	n/a	A/A
    		- Dirt and damp prevention treatment applied. - We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing. - Please note that during washing the damp- and dirt prevented treatment will disappear faster.						



Textaafoam b.v.
La Défense 11 | 5026 SC Tilburg
P.O. Box 12 | 5050 AA Goirle
The Netherlands

T +31(0)13 534 5934
F +31(0)13 534 7586
E info@textaafoam.nl
www.textaafoam.nl