Salsa



Textaafoam
Expect what's next in furniture fabrics | Comfort

Salsa

Salsa adds a lively yet refined touch to any interior, much like its namesake dance. With a perfect blend of softness, texture, and subtle shine, this upholstery fabric from the Textaafoam Comfort Collection brings swung to any piece of furniture.

The ultra-soft pile fabric features subtle stripes that add depth, while a delicate sheen enhances its appeal. Its voluminous texture gives furniture a full, inviting appearance, making it a perfect match for many designs. The carefully selected neutral colour palette ensures effortless integration into any space.

Salsa is crafted from 100% polyester for a long-lasting performance while maintaining its soft and comfortable touch. During use a sitting mirror/ seat depression may appear, this can be minimized by brushing Salsa on a regular base, against the pile (back to its original position). Important is to mention that this can never be taken away completely, as it is a property of such type of yarns.

This article can be applied widely, perfect for loose fitting upholstery, as well as for tight fitted furniture. Whether used on sofas, beds, chairs, or other furniture pieces, it brings a refined look to any piece of furniture. Salsa is also machine-washable at 30 degrees Celsius*.

The rib of this article is 6 mm and the base fabric in between 2,5 mm.

- Always be careful with sharp or rough objects such as watches, buckles, or Velcro, as they may damage the fabric.

- Consult the washing instructions of your furniture or covers before cleaning.

- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.

Textaafoam originals *Established in 1970, this Dutch family business brings together craftsmen in textiles and furniture design to build an unrivalled portfolio in upholstery fabrics that meets buyer's needs every time. Featuring a wide colour range, ultimate value for money and excellent reliability in the supply chain.*

Composition

/ faceside 100%PES
/ backside 100%PES
/ chenille jacquard

Suitable for

sofa's, beds, chairs with fitted and loose fitting upholstery



darkgrey 68



linen 110



liver 10



onyx 169



oyster 175



plumb 168



shitake 124



wood 108

Please note: colours may vary according to your screen settings.

Salsa - Article passport

An ultra-soft pile fabric with subtle stripes that add depth to a voluminous texture.

Available from stock in a wide range of contemporary and commercial colours.

Product characteristics

Productgroup	chenille jacquard	
Applications	sofa's, beds, chairs with fitted and loose fitting upholstery	
Composition faceside	100%PES	
Composition backside	100%PES	
Bonding	fleece	
Statistic code	58013600	
Dyeing method	yarn dyed	
Available colours	8	
Packaging	bubble wrap	

Durability specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Dry	Wet	DGM	DGM+	
Abrasion resistance - yarn breakage	DIN EN ISO 12947-1:2007-04, DIN EN ISO 12947-2:2017-03	CTL	cycles	>100.000		min. 12.000	min. 16.000	A
Pilling	DIN EN ISO 12945-2:2000-11. 2000 cycles	CTL	grade	4-5		min. 3-4	min. 4	A
Colour fastness to light	DIN EN ISO 105-BO2:2014-11. Process 3, exposure level 5							
	light colours	CTL	grade	5		min. 4	min.5	B
	middle colours	CTL	grade	5		min. 4	min.5	B
	dark colours	CTL	grade	5		min. 4	min.5	B
Colour fastness to rubbing	DIN EN ISO 105-X12:2016-11							
	light colours	CTL	grade	5	5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
	middle colours	CTL	grade	4-5	4-5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
	dark colours	CTL	grade	4	4-5	dry: 4, wet: 3	dry: > 4, wet: 3-4	A/A
Ignitability (cigarette test)	BS 5852 part 1 (1979) from The Furniture and Furnishing (Fire) (Safety) regulations: 1988 No. 1324. Schedule 4 part 1 Ignition source 0: cigarette	CTL		passed				

Processing specifications

Minimum workable width in centimeters	± 140
Roll length in meters	± 30
Material weight in grams per linear meter	± 682

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Tensile strength	DIN EN ISO 13934-1:2013-08	CTL	Newton	1.983	1.773	min. 350	min. 400	A/A
Tear growth resistance	DIN EN ISO 13937-3:2000-06	CTL	Newton	123,5	136,4	min. 25	min. 30	A/A
Resistance to seam slippage	DIN EN ISO 13936-2:2004-07. Load 180 N	CTL	mm	1,0	1,0	max. 5	max. 4	A/A
Delamination	DIN 53530:1981-02	CTL	Newton	28,5	17,6	n/a	n/a	n/a
Chemical substances	REACH	Centexbel		passed				
	Oeko-Tex, product class II	Centexbel		certified				

Cleaning specifications

Test	Test specification	Executed by laboratory:	Unit	Testresult		Norm RAL GZ 430/4:2019-01		Norm DIN EN 14 465:2006-09
				Warp	Weft	DGM	DGM+	
Dimensional change for washing 30 degrees celcius / air drying	DIN EN ISO 5077:2008-04, DIN EN ISO 6330:2013-02, DIN EN ISO 3759:2011-08	CTL	%	-1,0	-2,0	n/a	n/a	A/A

- We recommend to wash the cover inside out and immediately place the cover back to the piece of furniture, slightly damp, after washing.

Textaafoam b.v.
La Défense 11 | 5026 SC Tilburg
P.O. Box 12 | 5050 AA Goirle
The Netherlands

T +31(0)13 534 5934
F +31(0)13 534 7586
E info@textaafoam.nl
www.textaafoam.nl

okt 2026